



13.3 Digital signage

31.5 Digital signage

- * Low power consumption
- * Flexible power options (AC adapter, internal battery, external power bank)
- * Extended color gamut
- * Wide operating temperature range
- * Multiple connectivity options (Wi-Fi, LTE, MicroSD card)
- * Slim and narrow bezel design



31.5" Spectra 6 Signage

**Low energy
consumption**

**Support Wi-Fi
MicroSD card**

Faster update times

Android12

**CMS server performs
remote content updates**

**High contrast
electrophoresis imaging film**

31.5" Specification

Item	Description
Model	SA3P02
Display	31.5" E Ink Spectra 6
Resolution	2560 x 1440 (16 : 9)
PPI	94 PPI
Contrast Ratio	>20
Color	6 colors (B/W/Y/R/G/B)
Tempered Glass	1.8mm Glass with AR coating
Wireless Interface	Wi-Fi
Memory size	eMMC 32GB
	LPDDR4X, 4GB
LED	one
ID	USB-C port, MicroSD slot
Charging Type	Three options choice a. NTX battery box b. Power bank c. Power adapter
Battery Changeable	Yes
Storage Temperature	-25~60°C
Operating Temperature	0~50°C
Dimension (WxHxT)	707.9 *413.2 *23.5 mm
Weight	About 5.10Kg
Display mode	<ul style="list-style-type: none">● Auto slide show via MicroSD card● CMS: Access contents on cloud server via Wi-Fi● NAS: Access contents on NDS via HTTP GET
Development tool	<ul style="list-style-type: none">● Android 12 SDK with EPD sample codes● Power management: Provide control interface for device suspend/resume/sleep/wake up● Ability to access Android settings under Windows OS using optional control board (sold separately) and Scrcpy application.